



Data sheet KTZ21.5-51



CWL: Continuous running water level



Specification

Electric submersible pump KTZ-series

Degree of protection IP 68

Pressure resistance max. 25 m

Type of impeller Semi-open

Max. solid handling 8,5 mm

Suitable for:

spring-/rain-/waste-/ground water, water containing sand

Electric motor

Dry-type submersible induction motor

Insulation class F 2Poles 2840 1/min

Starting mode Direct starting

Rated voltage 400 V 50 Hz 3~

Power uptake 2,17 kW

Rated power 1,50 kW

Rated current 3,5 A

Start current 22,0 A

Cable

20m NSSHÖU 4Cx1,5mm²

Motor Protection

Circle thermal protector

(snap-action bi-metal device)

Shaft seal

Double inside mechanical seal in oil bath
additional lubrication by oil lifting device

Primary seal

Silicon carbide on silicon carbide

Secondary seal

Silicon carbide on silicon carbide

Bearings

Shielded ball bearings, maintenance-free

Materials

Impeller	Chromium Iron HiCrFC
Pump casing	FC200 (EN-GJL-200)
Suction cover	FCD50 (EN-GJS-500-7)
Motor Frame	FC150 (EN-GJL-150)
Shaft	SUS420J2 (EN-X30Cr13)

Discharge size

2" (50mm) Hose Coupling / BS-Coupling (optional)

Weight

35 kg (dry weight of the pump only without cable)

Performance curve



KTZ21.5-51

Discharge port	2"
Head	21,7 m
Flow	25,6 m³/h
Rated power	1,50 kW
Power input	2,17 kW
Phases	3~
Voltages	400 V
Frequency	50 Hz
Rated current	3,5 A
Starting current	22,02 A
Number of poles	2
Speed	2840 1/min
Starting mode	Direct starting
Insulation class	F



Dimensions

KTZ21.5-51




KTZ21.5-51

CWL: Continuous running water level
LWL: Lowest running water level

Sectional drawing

KTZ21.5-51



No.	Description	Remark	No.	Description	Remark
1	Cable	20m NSSHÖU	55	Rotor	.
20	Pump casing	FC200 (EN-GJL-200)	56	Stator	.
21	Impeller	Chromium Iron HiCrFC	64	Motor Frame	FC150 (EN-GJL-150)
22	Suction cover	FCD50 (EN-GJS-500-7)	68	Handle	Steelplate and rubber
23	Strainer	Steel plate	71	Shaft protection sleeve	SUS304 (EN-X5CrNi18-10)
25	Mechanical seal	H-20T			
26	Oil seal	DD25388			
30	Oil distributor	Plastic			
32	Discharge coupling	Aluminium die casting			
35	Oil screw	SUS304 (EN-X5CrNi18-10)			
36	Lubricant	Turbine oil (ISO VG32)			
50	Main cover	FC150 (EN-GJL-150)			
52A	Upper bearing	6204ZZC3			
52B	Lower bearing	6305ZZC3			
53	Motor Protector 380/400/415V-50Hz	KA314-HRXL00 (H.C)			
54	Shaft	SUS420J2 (EN-X30Cr13)			